

Model		MAP12C1PSP	
Power supply		Ph-V-Hz	115V,1Ph
Cooling	Capacity	Btu/hr	12000
	Input	W	1350
	Current	A	11.7
	EER	W/W	2.60
		Btu/W.h	8.90
Moisture Removal (26.7/20.9℃)		L/h	1.67
Moisture Removal (30/27.1℃)		L/h	0
Moisture Removal (35/28.3℃)		L/h	2.38
Starting current		A	50
Compressor	Model	ASM106E4UCZD	
	Brand	GMCC	
	Capacity	W	3260
	Input	W	1068
	Rated current(RLA)	A	9.68
	Locked rotor Amp(LRA)	A	55
	Thermal protector	UP3-67	
	Thermal protector position	INTERNAL	
	Capacitor	uF	70.9
	Refrigerant oil	ml	VG4/300
Indoor side fan motor	Model	YK16-90-4-14-1	
	Input	W	158.0
	Capacitor	uF	15
	Speed(hi/mi/lo)	r/min	1140/1070/970
	Capacitor class	P0	
	Insulation class	B	
	Waterproofing class	/	
Evaporator	a.Number of rows	3.0	
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)	Hydrophilic aluminum	
	e.Tube outside dia.and type	mm	Φ7Inner groove tube
	f.Coil length x height x width	mm	240x231x40.11
	g.Number of circuits	2	
Indoor side air flow (Hi/Mi/Lo)		m3/h	310/0/0
		CFM	182.35////
Indoor side noise level(Hi/Mi/Lo)		dB(A)	55.5/0/52.7
Condenser	a.Number of rows	3.0	
	b.Tube pitch(a)x row pitch(b)	mm	14.5x12.56
	c.Fin spacing	mm	1.2
	d.Fin type (code)	Unhydrophilic aluminium	
	e.Tube outside dia.and type	mm	Φ5Inner groove tube
	f.Coil length x height x width	mm	240x261x37.68
	g.Number of circuits	2	
Outdoor side noise level (Hi)		dB(A)	61
Refrigerant type		ozs	R410A
Design pressure		MPa	///
Plug type		LCDI(5-15P)	
Power cord type		14#x3	
Power cord length		mm	1900
Power cord length		ft	6.23
Control type		遙控式(Remote Control)	
Operation temp (room temp.)		℃	17-35
		℉	/
Application area (Cooling Standard)		m ²	16/23
Application area (Cooling Standard)		sq.ft	172.22/247.57
Application area (Cooling EPA)		sq.ft	
Application area (Cooling Standard) DOE		m ²	///
Application area (Cooling Standard) DOE		sq.ft	///
Dimension (W*D*H)		mm	355x345x703
		in	13.98x13.58x27.68
Packing (W*D*H)		mm	400x390x880
		in	15.75x15.35x34.65
Net/Gross weight		Kg	25.3/29.8
		lb	55.78/65.70
Loading quantity 20' /40' /40'HQ		Pieces	174/356/534

GRUPPO REFRIGERAZIONE CONDIZIONAMENTO S.p.A. DE CV