

AIRE ACONDICIONADO PORTATIL

Freyvën



FPQ121A

Frio/calor, 1 tonelada, 115-1-60

- Display digital
- Temporizador encendido/apagado
- Deshumidificador retira hasta 48lt en 24h
- Control remoto
- Refrigerante ecológico R-410Aa
- Operación silenciosa
- Modo Abanico 3 velocidades
- Panel de control
- Fácil instalación y mantenimiento
- Sistema de auto evaporación



52FPC121A

Solo Frio, 1 tonelada, 115-1-60

- Display digital
- Temporizador encendido/apagado
- Deshumidificador retira hasta 48lt en 24h
- Control remoto
- Refrigerante ecológico R-410Aa
- Operación silenciosa
- Modo Abanico 3 velocidades
- Panel de control
- Fácil instalación y mantenimiento
- Sistema de auto evaporación

AIRE ACONDICIONADO PORTATIL

MODEL		FPC121A	52FPQ121A
Control method		Remote	Remote
Power supply		115V/60Hz	115V/60Hz
Cooling capacity	BTU	12000	12000
	(W)	3277	3335
Heating capacity	BTU	\	9000
	(W)	\	2480
Rated cooling power	(W)	1167	1270
Rated cooling current	(A)	10.34	11.2
Rated heating power	(W)	\	1000
Rated heating current	(A)	\	8.8
EER for cooling	Btu*W/W		
	W/W	2.81	2.62
COP for heating	Btu*W/W	\	
	W/W	\	2.48
Moisture removal	L/h	2.6	2.56
Water tank volume	L	0.8	2
Air circulation volume	m3/h	350	350
Noise (H/M/L)	dB(A)		54/52/51
Refrigerant/Charge	g	R410A/540	R410a/600g
Exhaust hose pipe length	m	1.1	1.1
Applicable area	m2		
Compressor MFG		RECHI	Rechi
Compressor Model		39A231AD&59KB	44A231BG&FEKC
Compressor LRA	A	37	50.5
Compressor type		ROTARY	Rotary
Protection Class		IPX0	IPX0
Body dimension WxHxD	mm	270*695*480	463*773*372
Packing dimension WxHxD	mm	335*865*540	500*865*460
Net weight	kg	30	32
Gross weight	kg	33	39
Loading Capacity	20"/40"/40"HQ	148/304/456	110/240/360